



Emerson Impact Partner

(724) 746-3700
www.eci.us

Fisher Valves Accessory

ACOUSTIC BLANKET INSULATION

Shannon Global Energy Solutions LT450A-TT



Removable and Reusable

- 4-8 dBA Reduction
- Surface Temperatures Up to 450°F
- Double Sewn and Binded Seams
- Durable PTFE Teflon® Impregnated Fiberglass Cloth
- High Density Mass Loaded Vinyl (reflection)
- High Density Needled Fiberglass Mat Filler (absorption)
- ID Tag-Aluminum Nameplate, Embossed Lettering with Tag Description
- Stainless Steel Lacing Hardware with Wiretwist Fastener
- Vibration resistant
- Tested to ASTM E1222/ ISO-15665 Standards
- Expect a 15 year service life





Emerson Impact Partner



EMERSON™

Fisher Valves

ACOUSTIC BLANKET INSULATION

Acoustic Packages Available for:

1-150-Fisher-E-Control Valve
1-300-Fisher-E-Control Valve
1.5-150-Fisher-E-Control Valve
2-600-Fisher-E-Control Valve
3-600-Fisher-E-Control Valve
4-600-Fisher-E-Control Valve
6-600-Fisher-E-Control Valve
8-600-Fisher-E-Control Valve
2-150-Fisher-V150-Control Valve
3-150-Fisher-V150-Control Valve
4-150-Fisher-V150-Control Valve
6-150-Fisher-V150-Control Valve
8-150-Fisher-V150-Control Valve
1.5-150-Fisher-V200-Control Valve
2-150-Fisher-V200-Control Valve
3-150-Fisher-V200-Control Valve
4-300-Fisher-V200-Control Valve
4-150-Fisher-V200-Control Valve
4-600-Fisher-V200-Control Valve
6-150-Fisher-V200-Control Valve
6-600-Fisher-V200-Control Valve
8-600-Fisher-V200-Control Valve
10-600-Fisher-V200-Control Valve
2-300-Fisher-V300-Control Valve
3-300-Fisher-V300-Control Valve
4-150-Fisher-V300-Control Valve
6-300-Fisher-V300-Control Valve
10-600-Fisher-V300-Control Valve

Custom Blankets are also available.

Thickness
1" (2.5CM)

Surface Mass
1.8 lb/ft² to 2.8 lb/ ft² (8.8-13.7kg/m²)

Noise Attenuation
As High as a 8 dBA Reduction